


## Technical Data Sheet

Version 1.2 / 13.03.25

# Acrylic Eggshell



Product Code: CAEWE



### Product Description

**Acrylic Eggshell** is a premium quality, high performance, 100% acrylic, water-based, mid-sheen finish suitable for use on interior walls, ceilings and most plaster and wood surfaces. It is quick-drying with a low-odour and is non-yellowing.

### Intended Use

Recommended for use in high condensation situations and all high traffic areas such as kitchens, bathrooms, hotels, hospitals, nursing homes, schools and public buildings.

### Product Information

<b>Colours:</b>	An extensive range of colours through our tinting system
<b>Finish:</b>	Mid-Sheen Finish
<b>Specific Gravity:</b>	1.267 g/cm <sup>3</sup>
<b>Volume Solids:</b>	35%
<b>Practical Coverage:</b>	Approx. 10-14 sqm/litre Depending on the porosity of the surface
<b>VOC / Litre:</b>	EU limit value for this product (cat A/i): 30 g/l [2010]. This product contains max 30 g/l VOC

### Application Details

<b>Application</b>	Stir well. Seal absorbent surfaces with a pre-coat of Acrylic Eggshell thinned with up to 10% water. <b>Note:</b> Do not apply if temperature is below 10°C.
<b>Application Method</b>	Brush or Roller
<b>Cleaning</b>	Remove as much product as possible before cleaning. Clean equipment immediately after use in warm soapy water.

### Drying Time

<b>Touch Dry:</b>	1-2 Hours
<b>Re-Coat:</b>	Approx. 4 Hours
<b>Note:</b>	Drying/curing times depend on ambient temperature and relative humidity.



## Technical Data Sheet

Version 1.2 / 13.03.25

**Acrylic Eggshell**

Product Code: CAEWE

### Surface Preparation

Surfaces must be clean, dry and free from loose and flaking material. Prime bare surfaces with an appropriate primer. Sand down previously glossed surfaces with fine abrasive paper and clean thoroughly before applying a first coat of Castle Paints Acrylic Primer Undercoat. Wear a suitable mask if dry sanding.

### Storage & Handling

**Storage:** Always store and transport in a secure upright position. Store the closed container in a cool dry place.

**Pack Size:** 10L

### Health & Safety

Water Borne paint. Non-flammable.  
Ensure good ventilation during application and drying.  
Avoid contact with skin and eyes.  
In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
After contact with skin, wash with plenty of soap and water or a recognised skin cleanser. Do not use solvent.  
When spraying, do not breathe spray, wear suitable respiratory protective equipment.  
Keep out of reach of children.  
Do not empty into drains or watercourses.  
Avoid release to the environment.  
See MSDS for more information

### Quality Assurance

Castle Paints products are manufactured using only the highest quality raw materials. We guarantee the quality of our products. This guarantee does not include labour or cost of labour for the application of any paint.

The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Castle Paints be liable for consequential or incidental damages.

*The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Castle Paints be liable for consequential or incidental damages.*