



ESTABLISHED 1985

TECHNICAL DATA SHEET

Version 1.1 / 01.12.2019

Acrylic Premium Matt

Product Description	Acrylic Premium Matt is formulated on a tough, durable, acrylic resin which provides a top quality finish for interior walls and ceilings. It is designed to give a uniform finish that minimises surface imperfections.	
Technical Data	Colours:	An extensive range of colours are available through our tinting system
	Pack Size:	1 Litre, 2.5 Litre, 5 Litre, 10 Litre.
	Finish:	Matt Finish
	Volume Solids:	33%
	Film Thickness:	Wet: 75mm Dry: 25mm
	Practical Coverage:	Approx. 10-14 sqm/litre depending on the porosity of the surface
	VOC:	EU limit value for this product (Cat A/a): 30 g/l [2010]. This product contains max 30 g/l.
Surface Preparation	Surfaces must be clean, dry and free from grease. Remove any paint that is loose or flaking. Prime where required with an appropriate primer. Sand down any glossy surfaces until matt using fine waterproof sandpaper.	
	Wear a suitable mask if dry-sanding.	
Application Details	Stir well. Suitable for application by brush, roller or spray. Do not thin, except when spraying or o absorbent surfaces when a small quantity of water may be added, usually no more than 10%.	
	Do not apply if temper	rature is below 10°C.
Drying Time	Touch Dry:	1-2 Hours
	Re-Coat:	Approx. 4 Hours
	Note: Drying/curing times	depend on ambient temperature and relative humidity.
Cleaning	Remove as much product as possible before cleaning. Clean equipment immediately after use in warm soapy water.	
	Do not empty product into drains or watercourses.	





ESTABLISHED 1985

TECHNICAL DATA SHEET

Version 1.1 / 01.12.2019

Health & Safety	Keep out of reach of children	
	Ensure good ventilation during application and drying	
	After contact with skin, wash immediately with water	
	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice	
	Dispose of container or contents in accordance with local/national regulations	
	Always store and transport in a secure upright position. Protect from frost	
	Safety Data Sheet available on request	
Quality Assurance	Castle Paints products are manufactured using only the highest quality raw materials. We guarantee the quality of our products. This guarantee does not include labour or cost of labour for the application of any paint	



The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/ her own particular purpose. In no event shall Castle Paints be liable for consequential or incidental damages.