

## Technical Data Sheet

Version 1.2 / 13.03.25

# Kitchen & Bathroom Paint



BRUSH  
APPLICATION



ROLLER  
APPLICATION



Product Code: CKBWE

### Product Description

**Kitchen & Bathroom Paint** is specially formulated to provide protection in areas of high condensation. It will give a tough, washable, mid sheen finish which as well as being resistant to the effects of moisture and steam, will also inhibit the formation of mould and mildew. It is suitable for use on interior walls, ceilings and most plaster surfaces. It is quick drying with a low odour.

### Intended Use

Recommended for use in high condensation situations and high traffic areas such as kitchens, bathrooms, hospitals, hotels, bakeries, nursing homes, schools and public buildings. However, it is not suitable for areas regularly soaked with water e.g. shower enclosures.

### Product Information

<b>Colours:</b>	An extensive range of colours through our tinting system
<b>Finish:</b>	Mid-Sheen Finish
<b>Specific Gravity:</b>	1.267 g/cm <sup>3</sup>
<b>Volume Solids:</b>	35%
<b>Practical Coverage:</b>	Approx. 10-14 sqm/litre Depending on the porosity of the surface
<b>VOC / Litre:</b>	EU limit value for this product (cat A/d): 130 g/l (2010). This product contains max 30 g/l VOC.

### Application Details

<b>Application</b>	Stir well. Seal absorbent surfaces with an appropriate primer (i.e. Primex Excel or Acrylic Premium Matt). Apply 2 coats of Kitchen and Bathroom paint each at 45° to the other, taking care to apply right into the corner of walls. <b>Note:</b> Do not apply if temperature is below 10°C.
<b>Application Method</b>	Brush or Roller
<b>Cleaning</b>	Remove as much product as possible before cleaning. Clean equipment immediately after use in warm soapy water.

## Technical Data Sheet

Version 1.2 / 13.03.25

## Kitchen & Bathroom Paint

Product Code: CKBWE

### Drying Time

**Touch Dry:** 1-2 Hours

**Re-Coat:** Approx. 4 Hours

**Full Cure:** 4-6 Days

**Note:** Drying/curing times depend on ambient temperature and relative humidity.

### Surface Preparation

Surfaces must be clean, dry and free from loose and flaking material. Prime bare surfaces with an appropriate primer. Sand down previously glossed surfaces with fine abrasive paper and clean thoroughly before applying a first coat of Castle Paints Acrylic Primer Undercoat. Wear a suitable mask if dry sanding.

### Storage & Handling

**Storage:** Always store and transport in a secure upright position. Store the closed container in a cool dry place.

**Pack Size:** 1L, 2.5L, 5L

### Health & Safety

Water Borne paint. Non-flammable.  
Ensure good ventilation during application and drying.  
Avoid contact with skin and eyes.  
In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
After contact with skin, wash with plenty of soap and water or a recognised skin cleanser. Do not use solvent.  
When spraying, do not breathe spray, wear suitable respiratory protective equipment.  
Keep out of reach of children.  
Do not empty into drains or watercourses.  
Avoid release to the environment.  
See MSDS for more information

### Quality Assurance

Castle Paints products are manufactured using only the highest quality raw materials. We guarantee the quality of our products. This guarantee does not include labour or cost of labour for the application of any paint.

The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Castle Paints be liable for consequential or incidental damages.

*The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Castle Paints be liable for consequential or incidental damages.*