

TECHNICAL DATA SHEET

Version 1.1 / 01.12.2019

Kitchen & Bathroom Paint

Product Description

Kitchen & Bathroom Paint is specially formulated to provide protection in areas of high condensation. It will give a tough, washable, mid sheen finish which as well as being resistant to the effects of moisture and steam, will also inhibit the formation of mould and mildew. It is suitable for use on interior walls, ceilings and most plaster surfaces. It is quick drying with a low odour.

Areas of Use: Recommended for use in high condensation situations and high traffic areas such as kitchens, bathrooms, hospitals, hotels, bakeries, nursing homes, schools and public buildings. However, it is not suitable for areas regularly soaked with water e.g. shower enclosures.

Technical Data

Colours:	An extensive range of colours are available through our tinting system
Finish:	Mid-Sheen Finish
Volume Solids:	35%
Film Thickness:	Wet: 80mm Dry: 30mm
Practical Coverage:	Approx. 10-14 sqm/litre depending on the porosity of the surface
VOC:	EU limit value for this product (cat A/d): 130 g/l (2010). This product contains max 30 g/l VOC.

Surface Preparation

Surfaces must be clean, dry and free from loose and flaking material. Prime bare surfaces with an appropriate primer. Sand down previously glossed surfaces with fine abrasive paper and clean thoroughly before applying a first coat of Castle Paints Acrylic Primer Undercoat.

Wear a suitable mask if dry-sanding.

Application Details

Stir well. Easily applied by brush or roller. Seal absorbent surfaces with an appropriate primer i.e. Primex Excel or Acrylic Premium Matt. Apply 2 coats of Kitchen and Bathroom paint each at 45° to the other, taking care to apply right into the corner of walls.

Do not apply if temperature is below 10°C.

Drying Time


Touch Dry:	1-2 Hours
Re-Coat:	Approx. 4 Hours
Full Cure:	4-6 Days

Note: Drying/curing times depend on ambient temperature and relative humidity.

Cleaning

Remove as much product as possible before cleaning. Clean equipment immediately after use in warm soapy water.

Do not empty product into drains or watercourses.



TECHNICAL DATA SHEET

Version 1.1 / 01.12.2019

Kitchen & Bathroom Paint

Health & Safety

Keep out of reach of children

Ensure good ventilation during application and drying

After contact with skin, wash immediately with water

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice

Dispose of container or contents in accordance with local/national regulations

Always store and transport in a secure upright position. Protect from frost

Safety Data Sheet available on request

Quality Assurance

Castle Paints products are manufactured using only the highest quality raw materials. We guarantee the quality of our products. This guarantee does not include labour or cost of labour for the application of any paint..



The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Castle Paints be liable for consequential or incidental damages.