



## PRIMEX ULTRA PRIMER

### 1. PRODUCT DESCRIPTION

**PrimeX Ultra** is a white pigmented shellac primer-sealer that primes and seals a multitude of surfaces. It is formulated to offer quick drying, superb adhesion and the best stain blocking technology available. This makes PrimeX Ultra the No. 1 choice for completing any paint job.

### 2. INTENDED USE

#### Priming

Primes plaster board, filled areas, wood, glossy surfaces and most other paintable interior surfaces. It is only suitable for spot priming exterior surfaces i.e. not for full surface exterior applications. It can also be used for priming knots and sap streaks on wood.

#### Sealing

Seals unpainted or porous interior surfaces so topcoats have better coverage. Very porous surfaces may require two coats. It also effectively seals all types of odours including musty odours from mould growth, pet urine and odours from flood and fire damage.

#### Stain Blocking

PrimeX Ultra offers the best available stain blocking technology including water stains, mould stains, smoke stains, rust stains, graffiti, crayon, ink and many other types of stains.

#### Adhesion

It adheres to glossy surfaces, panelling, MDF, varnish, lacquer, ceramic wall tiles and metal without sanding. (Cleaning and degreasing necessary).

### 3. TECHNICAL DATA

**COLOURS:** White - Tintable.

**FINISH:** Flat finish.

**VOLUME SOLIDS:** 30%

**FILM THICKNESS:** 30 microns dft approx.

**PRACTICAL COVERAGE:** Up to 12.5sqm per litre depending on porosity.

**VOC:/litre:** Max 500g/litre

### 4. SURFACE PREPARATION

Surface should be clean, dry, sound and free of dust, dirt, excessive chalky material, grime, grease, oil, wax, mould, wallpaper adhesive or any contamination that may interfere with adhesion. If unsure, always wash surface with a household cleaner, appropriate cleaning solution or methylated spirit. Remove any flaking coatings. Sand any remaining paint film edges smooth with the surface. For exterior spot-priming lightly sand exposed wood with 80 - 100 grit sandpaper to remove loose or weathered wood fibres. When priming over stained areas first attempt to remove as much of the stain as possible by washing, sanding, scrapping, etc. Remove interior mould with PrimeX Fungicidal Wash following instructions. Allow surface to dry completely before priming. Spot-prime and fill all nail holes with a filling compound. Wire brush rusty areas. Avoid the inhalation of dust, wear a suitable mask if dry sanding.



## PRIMEX ULTRA PRIMER

### 5. APPLICATION DETAILS

Shake or stir before using. Eliminate all sources of ignition. Apply with a natural or synthetic bristle brush, roller or sprayer. Follow manufacturer's instructions when using spray equipment. As a general rule DO NOT THIN the product, although, if PrimeX Ultra thickens in the container due to solvent evaporation, add a small amount of methylated spirit. When spraying, dilute with methylated spirit up to 2% - refer to technical data sheets.

The product can be applied in a variety of temperatures from – 10°C to + 30°C

### 6. DRYING TIME

Substrate Temperature	Touch Dry	Hard Dry	Minimum Overcoat	Maximum Overcoat
10 C	20 minutes	30 minutes	45 minutes	Unlimited

### 7. STORAGE & HANDLING

**STORAGE:** Store in a cool dry place and out of reach of children. Keep away from extremes of temperature.

**PACK SIZES:** 375ml, 750ml and 2.5 Litre.

### 8. HEALTH & SAFETY



Paint product - flammable. Keep out of the reach of children.

Keep container in a well ventilated place, away from sources of ignition - No smoking.

Use only in well-ventilated areas. Do not breathe vapour or spray. In case of insufficient ventilation wear suitable respiratory equipment. In case of contact with eyes rinse immediately with plenty of water. Remove splashes from skin using soap and water or a recognised skin cleaner. Do not take internally. Ensure container is stored in a secure upright position and tightly closed. Dispose of this material and its container at a hazardous or special waste collection point. Contains no added lead.

### 9. QUALITY ASSURANCE

PrimeX products are produced by Castle Paints using only the highest quality raw materials. We guarantee the quality of our products when applied according to directions. The directions apply to most applications, but may not cover special conditions, applications, techniques and/or surfaces. This does not include labour or cost of labour for the application of any paint. For more information refer to this product's safety data sheet or contact our technical department.



Cloncollig Industrial Estate,  
Tullamore, Co. Offaly, Ireland.

Tel: 057 93 51583

Fax: 057 93 51776

Visit: [www.castlepaints.ie](http://www.castlepaints.ie)