



SHIELDX SLATE PAINT

PRODUCT DESCRIPTION

- ENHANCES AND PROTECTS NATURAL AND FIBRE CEMENT SLATES
- WATERBORNE ACRYLIC COATING, FAST DRYING.
- SUPERIOR ADHESION PROPERTIES
- COATING IS FULLY ELASTIC AND BREATHABLE, ALLOWING WATER OUT BUT NOT IN.
- EXCELLENT RESISTANCE TO WEATHERING
- RESISTS FORMATION OF FUNGUS
- DRIES TO AN ATTRACTIVE SATIN MATT FINISH

ShieldX Slate Paint is a high performance, waterborne acrylic coating with high levels of elasticity, specially formulated for the refurbishment of roof slates, both natural and artificial fibre cement types.

VOC: EU limit value for this product (cat A/g): 30 g/l (2010). This product contains max 30 g/l VOC.

SURFACE PREPARATION

Slates should be clean, dry, sound and free from any dust, dirt, fungal growth or any contaminant that may interfere with adhesion. Wash down the surface with Castle Paints Fungicidal Treatment for the removal of moss etc. If using a power washer, it is important not to use it in such a way as to cause damage to the slates or any fixings. It is good practice to always perform an adhesion test.

N.B It is not recommended to apply ShieldX Slate Paint on artificial fibre cement slates that are too badly deteriorated. To check the mechanical stability of the slate; After cleaning use a screwdriver or sharp knife to see if the fibres have come loose on the surface of the slate, if they have then they cannot be coated and need to be replaced.

APPLICATION DETAILS

Stir thoroughly before use. Apply by brush, roller or airless spray. Temperature should be a minimum 8°C. Do not apply in full sun. Do not apply in damp conditions or if rain is expected within 4 hours.

For application to natural slates, apply two coats unthinned. For application to fibre cement slates, apply the first coat thinned with clean water no more than 15%, and the second coat unthinned.

COVERAGE: Theoretical coverage is 8-12 sq. metres per litre per coat. Practical coverage depends on factors such as porosity and roughness of the substrate, method of application and material losses during application.

DRYING TIME: At normal temperatures and weather conditions this paint will dry in 1-2 hours. Recoatable after 12 hours.

CLEANING: Clean all tools with warm water and liquid detergent/household cleaner and rinse well.

STORAGE & HANDLING

STORAGE: Always store and transport in a secure upright position. Store the closed container in a cool dry place.

Keep away from extremes of temperature.

PACK SIZE: 10 Litre.



SHIELDX SLATE PAINT

HEALTH & SAFETY

- Paint product. Keep out of reach of children.
- In case of contact with eyes rinse immediately with plenty of water.
- In case of insufficient ventilation wear suitable respiratory equipment.
- Wear gloves. Remove splashes from skin using soap and water or a recognised skin cleaner.
- Dispose of container and contents in accordance with local/national regulations.
- Do not empty product into drains or watercourses.
- Contains no added lead.
- See MSDS for more information.

QUALITY ASSURANCE

ShieldX products are manufactured by Castle Paints using only the highest quality raw materials. We guarantee the quality of our products. This guarantee does not include labour or cost of labour for the application of any paint.

The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Castle Paints be liable for consequential or incidental damages.