

## Technical Data Sheet

Version 1.2 / 03.03.25

# Slate Paint



SPRAY  
APPLICATION



ROLLER  
APPLICATION



BRUSH  
APPLICATION



Product Code: SXSP

### Product Description

**Slate Paint** is a high performance, waterborne acrylic coating with high levels of elasticity, specially formulated for the refurbishment of roof slates, both natural and artificial fibre cement types.

- Water-based
- Fast Drying
- Superior Adhesion
- Resists formation of fungus
- Resists Weathering
- Fully elastic & breathable

### Intended Use

For the refurbishment of roof slates, both natural and artificial fibre cement types.

### Product Information

Colours:	Black
Finish:	Satin-Matt Finish
Specific Gravity:	1.14
Volume Solids:	48%
Practical Coverage:	8 sq. metres per litre per coat. Coverage dependent on factors such as porosity, roughness of substrate, method of application & material losses during application.
VOC / Litre:	EU limit value for this product Cat A(d) 130g/l. This product contains <130 g/l VOC's

### Application Details

Stir thoroughly before use. Apply by brush, roller or airless spray. Temperature should be a minimum 8°C. Do not apply in full sun. Do not apply in damp conditions or if rain is expected within 4 hours. For application to natural slates, apply two coats unthinned. For application to fibre cement slates, apply the first coat thinned with clean water no more than 15%, and the second coat unthinned.

### Drying Time

At normal temperatures and weather conditions this paint will dry in 1-2 hours.  
Recoat after 12 hours.

## Technical Data Sheet

Version 1.2 / 03.03.25

**Slate Paint**

Product Code: SXSP

### Surface Preparation

Slates should be clean, dry, sound and free from any dust, dirt, fungal growth or any contaminant that may interfere with adhesion. Wash down the surface with Castle Paints Fungicidal Treatment for the removal of moss etc. If using a power washer, it is important not to use it in such a way as to cause damage to the slates or any fixings. It is good practice to always perform an adhesion test.

N.B. It is not recommended to apply Slate Paint on artificial fibre cement slates that are too badly deteriorated. To check the mechanical stability of the slate; After cleaning use a screwdriver or sharp knife to see if the fibres have come loose on the surface of the slate, if they have then they cannot be coated and need to be replaced.

### Storage & Handling

**Storage:** Always store and transport in a secure upright position. Store the closed container in a cool dry place.

**Pack Size:** 10 Litre

### Health & Safety

Paint product - flammable  
Keep away from sources of ignition  
Do not take internally  
Keep out of reach of children  
In case of contact with eyes rinse immediately with plenty of water  
In case of insufficient ventilation wear suitable respiratory equipment  
Remove splashes from skin using soap and water or a recognised skin cleaner  
Dispose of container and contents in accordance with local/national regulations  
Do not empty product into drains or watercourses  
Contains no added lead  
See MSDS for more information

### Quality Assurance

Castle Paints products are manufactured using only the highest quality raw materials. We guarantee the quality of our products. This guarantee does not include labour or cost of labour for the application of any paint.

The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Castle Paints be liable for consequential or incidental damages.

*The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Castle Paints be liable for consequential or incidental damages.*