


TECHNICAL DATA SHEET

Version 1.2 / 02.02.2022

T-Wash

Product Description	Castle Paints T-Wash is an etching wash for non-weathered, untreated, galvanised surfaces. It creates a chemical reaction and causes the surface to turn black, which confirms that the surface has been satisfactorily degreased and is ready for priming.
Surface Preparation	<p>Surfaces must be clean and free from anything that will interfere with the materials to be applied. Wash with hot water and liquid detergent solution to remove oil, grease or any other contaminants, frequently changing the water. Rinse thoroughly with clean water.</p> <p>Allow to dry. Galvanised surfaces should be pre-treated with Castle Paints T-Wash. Overall blackening of the surface will confirm satisfactory surface preparation.</p>
Product Information	<p>Composition: Acidic copper solution</p> <p>Finish: Not applicable</p> <p>Availability: 5L</p> <p>Colour: Blue solution</p> <p>Volume Solids: 1%</p> <p>Wet Film Thickness: Not applicable</p> <p>Dry Film Thickness: Not applicable</p> <p>VOC Content: Max 335g/l</p> <p>Flash Point: 36°C (closed cup)</p> <p>Theoretical Coverage: Up to 15 sq. metres/litre on smooth surfaces</p> <p>Limitations: Do not apply when air or substrate temperatures are likely to fall below 8°C or when the relative humidity is above 80% during application or the drying period</p>
Drying Time	Under normal drying conditions touch dry in 2 hours. Treated surfaces must be primed within 48 hours.
Application Details	Stir well before use. Apply, undiluted, by brush.
Cleaning	Return surplus material to container. Wash with clean water immediately after use.



TECHNICAL DATA SHEET

Version 1.2 / 02.02.2022

T-Wash

Health & Safety

Paint product - flammable

Keep away from sources of ignition

Do not take internally

Keep out of the reach of children

In case of contact with eyes rinse immediately with plenty of water

In case of insufficient ventilation wear suitable respiratory equipment

Remove splashes from skin using soap and water or a recognised skin cleaner

Dispose of container and contents in accordance with local/national regulations

Do not empty product into drains or watercourses

See MSDS for more information

Quality Assurance

Castle Paints products are manufactured using only the highest quality raw materials. We guarantee the quality of our products. This guarantee does not include labour or cost of labour for the application of any paint.



The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Castle Paints be liable for consequential or incidental damages.